

3 Series

24.72 hp (18.2 kW)-42.2 hp (31 kW)
Compact Utility Tractors

The mighty 3 reaches a new level

The 300E Mechanical Self-Leveling option starts level and stays level the easy way. See inside.



JOHN DEERE

Meet The Mighty Three.

Get to know John Deere 3 Series Compact Tractors. This lineup features the 3D, the economical 3E and the phenomenal 3R. Page after page, you'll find design innovation and exceptional engineering as well as attachments and implements that help you get the job done. [Check out the 3s.](#)

300E MSL LOADER

Keeping a bucket or pallet level is easier with a Mechanical Self-Leveling (MSL) option on a 300E loader when compared to a non-self-leveling (NSL) 300E loader. In fact, the lift capacity of an MSL loader is 1283 lbs (583 kg) measured 19.7 in (500 mm) ahead of the pivot. That's a 34% increase when compared to the 300E NSL Loader. Start level and stay the easy way with an MSL loader today.





The 3D

The latest addition to the 3 Series comes in strong with a **gear drive transmission** and a **standard 4409 lb (2000 kg) hauling capacity**. That's something simple and powerful to hitch your wagon to. Check out the 3D on page 3.



The 3E

This 3 is **economical** and **capable**. The operator station is wide and comfortable. The turning radius, tight at 44 in. (111.76 cm). Get all the details on page 5.



The 3R

Premium, top-of-the-line and powerfully versatile. That's the 3R. The **optional cab has heat and AC**. The PowrReverser™ option makes loader work easy. The optional **AutoConnect™ Mid-mount mower deck** is simplicity itself. Learn all about our most powerful mid-PTO (Power Take Off) tractor on page 7.

6-YEAR LIMITED POWERTRAIN WARRANTY¹

¹ All Compact Utility Tractors purchased new from an authorized John Deere Dealer come standard with a 6 year/2000 hour (whichever comes first) Powertrain Warranty. See the Limited Warranty for New John Deere Turf & Utility Equipment at dealer for details.

Get to know the
mighty three. See which model
is right for you. Or visit
JohnDeere.com/3Series or
JohnDeere.ca/3Series or
your John Deere
dealer today.

THE 3D

3025D, 3035D, 3043D

62 IN. (157.4 CM) WHEELBASE

The 49.3 in. (125.4 cm) track width and up to 2800 lb (1271 kg) weight helps with tractor stability on uneven terrain and hillsides. Particularly when towing a wagon.

SIMPLICITY AND POWER. ALL IN A COMPACT SIZE.

That's the mighty 3D. The simplicity starts with a heavy-duty drivetrain, 8F/8R, gear drive transmission. Very easy to learn and use with column and fender mounted shifters. Then there's the muscle with 24.72 HP² (18.2 kW²), 34.7 HP² (25.5 kW²) or 42.2 HP² (31 kW²) options and a powerful, standard 4409 lb (2000 kg) hauling capacity. That doubles what other comparable small tractors can do.

Add the compact size and you have a small tractor designed to pull through narrow tracts. It can go places easily its bigger brothers cannot. This small tractor is perfect for large properties, tree nurseries, vineyards, orchards, almond farms and spinach farms or any other property that needs to move heavy crop or materials from here to there.

**6-YEAR
2,000 HOUR
LIMITED
POWERTRAIN
WARRANTY¹**

¹ All Compact Utility Tractors purchased new from an authorized John Deere Dealer come standard with a 6 year/2000 hour (whichever comes first) Powertrain Warranty. See the Limited Warranty for New John Deere Turf & Utility Equipment at dealer for details.

² The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information. Rated engine horsepower (ISO) per SAE J1995.



**300E LOADER AND DRAWBAR FOR
LOADER WORK AND HAULING WAGONS.**



**OPTIONAL FRONT WEIGHTS
FOR BALLASTING.**



63.6 IN (161.5 CM) TURNING RADIUS.
As measured from the inner rear tire
with a 300E loader. To maneuver
around tight spaces. Add optional pallet
forks for even more versatility.

HELP YOURSELF

Our full list of implements
and attachments would
rival the longest to-do list.
Let **TipsNotebook.com**
show you how to use them.

LET THE MIGHTY 3 PULL THROUGH



300E LOADER

with a Mechanical Self Leveling
Loader (MSL) option has a lift
height of 84 in. (214 cm) and a
lift capacity of 1283 lb (539 kg)
measure at 19.7 in (500 mm)
ahead of the pivot, so you can
shoulder just about anything.
Non Self-Leveling
option available.

Pull wagonload of material
across narrow, tight tracts. The heavy
duty components are the key to the
4409 lb (2000 kg) hauling capacity.

14 in. (35 cm) Ground Clearance. Get a smoother ride
and avoid getting stuck going over uneven terrain.

1670 lb (757.4 kg) Hitch Capacity. That's some serious muscle.

Fender Mounted Gear Shift Lever. Right at hand. Instead of awkwardly
placed between your legs.

Forward Reverse (F/R) Lever is column mounted next to the steering
wheel, so changing directions is easy and at your fingertips.

The 9.7 U.S. gal. (36.7 L) Fuel Tank is at the back of the tractor for
easy access. It holds enough diesel fuel for a full, 8-hour day's work.³

1200-Hour Transmission Fluid Service Interval. That's more time
in the field and less time in the shop performing maintenance.

Service Advisor onboard diagnostics identify issues and help
direct repairs.

Telescoping Draft Links Option. Connect attachments
and implements to the back of your tractor without constantly
readjusting.

John Deere Quik Knect™ Option. This is the easy way to connect
most PTO powered implements and attachments to the back of
your tractor without scraping your knuckles.

Light It Up. Night becomes day with optional halogen work lights
or high-performance LED work lights.

THE ULTIMATE WAGON HAULER. Plenty of low-end grunt.
Thanks to the heavy-duty drivetrain and the large spiral bevel gear.

³ Performance varies based on engine load requirement. Fuel consumption varies based on engine load.

THE 3E

3025E, 3032E, 3038E

THE OPEN OPERATOR STATION IS WIDE AND COMFORTABLE and the seat is a command chair. The controls are intuitive and clearly labeled.

PERFECT TO DIG INTO TO-DO LISTS.

These 24.72 HP² (18.2 kW²), 31.1 HP² (22.9 kW²), or 37.2 HP² (27.4 kW²) small farm and landscape tractors are economical and versatile. Perfect to dig into to-do lists.

Economy and quality are strengths here. The operator station is wide and comfortable. Other popular features include power steering for maneuverability and a tight turn radius. You'll also get terrain-hugging four-wheel drive and the forward/reverse Twin Touch™ pedal system. Because changing directions is easy with separate pedals. One for forward. The other for reverse.

Tire chains and wheel weights offer additional traction.

**6-YEAR
2,000 HOUR
LIMITED
POWERTRAIN
WARRANTY¹**

¹ All Compact Utility Tractors purchased new from an authorized John Deere Dealer come standard with a 6 year/2000 hour (whichever comes first) Powertrain Warranty. See the Limited Warranty for New John Deere Turf & Utility Equipment at dealer for details.

² The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information. Rated engine horsepower (ISO) per SAE J1995.



3025E

OPTIONAL CANOPY to provide cover from the sun or rain.



370B BACKHOE (available on 3E models only). These Backhoes have a reach of nearly 10 ft. (304.8 cm) and can dig down 6 ft. 10 in. (208.3 cm). Dig in.



OPTIONAL 300E LOADER with a Mechanical Self Leveling Loader (MSL) option has a lift height of 84 in. (214 cm) and a lift capacity of 1283 lb (539 kg) measure at 19.7 in (500 mm) ahead of the pivot, so you can shoulder just about anything. Non Self-Leveling option available.

HELP YOURSELF

Our full list of implements and attachments would rival the longest to-do list. Let TipsNotebook.com show you how to use them.



3038E

Shown with Light Guards and LED Lights.

LET THE MIGHTY 3 MAKE SHORT WORK OF YOUR TO-DO LIST

The Power Steering is fueled by a dedicated hydraulic pump. Something you'll appreciate when you've got some serious loader work to do.

The Generous Ground Clearance helps you avoid getting stuck and gives you a smoother ride on uneven terrain.

Liquid-Cooled Diesel Engines. These efficient diesel engines offer deep reserves of torque for handling tough loads.

The Fuel Tank is at the back of the tractor for easy access. Also, having the fuel tank away from the hood isolates the fuel and allows for top engine performance.

12-Volt Outlet. Mounted on the right fender to provide power at need.

Service Advisor onboard diagnostics identify mechanical problems and help direct repairs.

Engine Access is as easy as 1-2-3-4 with four quarter fasteners on the engine panel. Plus, side panels may be removed without tools in under a minute.

1200-Hour Transmission Fluid Service Interval. That's more time in the field and less time performing maintenance in the shop.



THE STANDARD FOUR-WHEEL-DRIVE and differential lock add traction to help negotiate sandy soil, mud, snow and tough chores.

THE 3R

3033R, 3039R, 3046R

POWRREVERSER™ TECHNOLOGY.

Features no-stop forward-to-reverse shifting with the flip of a lever. Designed to simplify tasks requiring frequent directional changes, such as loader work.

The 3R IS STRONG WITH 32.2 HP² (23.7 KW²), 38.7 HP² (28.5 KW²), AND 45.3 HP² (33.3 KW²) OPTIONS.

Choose between a hydrostatic transmission or a PowrReverser™ option. With the PowrReverser™, you'll get precise hydraulic control, the foundation of loader work efficiency and smoothness. Comfort features include a suspension seat, adjustable steering wheel and intuitive, color-coded tractor controls.

But that's not all. These machines are built right. The durable, heavy-duty frame and solid weight provide exceptional power to the ground. The standard four-wheel drive and power steering offer ground-gripping maneuverability and traction in dirt, mud, snow or sand. The options are even strong, including a climate controlled cab for all weather work and an optional Drive-Over AutoConnect™ Mid-Mount Mower Deck. Because the tractor is a John Deere, mowing is always a strength.

**6-YEAR
2,000 HOUR
LIMITED
POWERTRAIN
WARRANTY¹**

¹ All Compact Utility Tractors purchased new from an authorized John Deere Dealer come standard with a 6 year/2000 hour (whichever comes first) Powertrain Warranty. See the Limited Warranty for New John Deere Turf & Utility Equipment at dealer for details.

² The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information. Rated engine horsepower (ISO) per SAE J1995.



THE OPTIONAL CAB WITH HEAT AND AC.

All weather. Any season.
All the time.

Optional backup alarm, horn kit, rear wiper kit, radio, and more are available for 3R cab tractors.

3033R



OPTIONAL REAR SPREADER AND FRONT SNOW BLOWER, great for salting parking lots or spreading fertilizer.

Forward/
Reverse
Twin Touch™
Pedals.



Intuitive
controls.



Easy to
maintain
and service.



HELP YOURSELF

Our full list of implements and attachments would rival the longest to-do list. Let TipsNotebook.com show you how to use them.

3046R



LET THE MIGHTY 3 COME THROUGH WITH THE BEST OF EVERYTHING

THE FINAL TIER 4 EMISSIONS COMPLIANT, LIQUID-COOLED DIESEL ENGINE
Tested over thousands of hours, under heavy loads, with temperatures as low as -28 °F (-33 °C).
It's ready for your job.

Standard Automotive-style Cruise Control keeps a constant speed.

Forward/Reverse Twin Touch™ Pedals
One pedal to go forward. Another to go backward.

LoadMatch™ Technology prevents engine stall during heavy load applications.

MotionMatch™ Technology fine tunes transmission responsiveness with the turn of a dial.

SpeedMatch™ Technology pre-sets a maximum speed. Perfect for low-speed applications.

eThrottle™ Technology increases engine RPM and tractor speed simultaneously, for maximum performance while preserving fuel.

The 60D or 72D Drive-Over AutoConnect™ Mid-Mount Mower Deck.
Simply drive over this large mower deck—then drive off with it—and get mowing.

Quick-Attach Backhoes. Install this backhoe within minutes while not removing 3-pt hitch components. And dig in.

Quik-Park™ 300R and 320R Loaders can be attached and detached (with an integrated parking stand) in less than three minutes with no tools.



OPTIONAL FRONT-HITCH AND FRONT PTO give you more flexibility to accomplish your tasks. Perfect for snow blowing.

² The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information. Rated engine horsepower (ISO) per SAE J1995.



iMatch™ Quick-Hitch

Connect attachments and implements the easy way.



John Deere Quik-Knect™

The easy way to connect rotary cutters, tillers and other PTO-driven implements.



TractorPlus™ app.

Better tools. Better information. It's all the better with the TractorPlus™ App. You'll get maintenance recommendations, tutorial videos and more.

Available on all 4 Series Tractors. Download at the Apple Store or at Google Play.

The Smart Connector option enhances the user experience of the TractorPlus™ app by adding several features that help operators use and maintain equipment more efficiently.

Tool storage. It's like having a tool box built right into your tractor.



Third Function Loader Hydraulics. Add functionality and control for greater bucket and blade manipulations.

Additional Selective Control Valves provide additional hydraulic outlets to allow for multiple functions on various implements.

Power Beyond Kits⁴

The hydraulic connections you need to hook up your backhoe and wood chipper.

⁴For backhoes and wood chippers.

Implements

LET THE MIGHTY 3 GET IT DONE.

From backhoes to wheel rakes to snowblowers and mower decks, John Deere and Frontier commercial-grade implements do it all, with precision, fast. Thanks to John Deere iMatch™, Quik-Park™ loaders and drive-over mower decks. Many, many, many implements are ready and waiting. Visit JohnDeere.com, JohnDeere.ca, or talk to your John Deere dealer today. Here's a short list to get you started:



Loaders

Everything from buckets to pallet fork attachments. Loader work is 3 Series territory. The 300E Loader features Mechanical Self-Leveling and Non-Self-Leveling options. The 300R and 320R feature an integrated parking stand to simplify attachment and detachment.



Backhoe

Provides precise control and extra torque when back-filling, superior visibility to the trench and powerful digging force.

Optional Attachments:
Mechanical thumb, ripper point and 8 in. trenching bucket.



Rotary Cutter

Because cutting grass and brush is just one of many tasks. Grooming mowers also available.



Drive-Over AutoConnect™ Mid-Mount Mower Deck or OnRamp™ Mower Deck

Cuts grass down to size and is easy to attach. [3R Only]



Disk (3 Point)

To control weeds in low-lying areas that can't be sprayed or seeded.



Rotary Tiller

Commercial-grade with heavy-duty tine shafts to loosen even the most packed-down soil.



Core Aerator

Keep grass roots healthy. Allows oxygen in the ground and opens the soil to accept fertilizer.



Overseeder

To spread everything from seed to fertilizer to sand.



Post Hole Digger & Augers

Installing a new fence? Dig deep and wide, tree roots and all, for your posts.



Front Blade

Moves dirt or gravel and clears snow. Angle right or left to make the job easier. Box blades, rear blades, landscape rakes and land planes also available.




Cultipacker

To firm and smooth seedbeds after disking.

Attachments

LET THE MIGHTY 3 DO MORE.

Whether it's enhanced productivity, stability, visibility, or hours in the field, these attachments will help you get the most out of your 3 Series Tractor.



Forward Lighting Kit, Rear Work Light and 360° LED Lighting

Enjoy increased visibility when working in low-light conditions. Lights mount to brush guards located on the ROPS.



Lighting Brush Guard Kits (Two Guards)

Available for both the warning lights and LED lighting options.



Engine Coolant and Transmission Oil Heaters

For cold weather operation, be ready with these kits to warm your machine.



Canopies

ShadePro™ Canopy Sun protection with an adjustable fan. Keep cool while keeping debris off you. Installed to the ROPS.



Mirror Kits

For greater visibility of what's behind you while focusing on what's ahead.



Ballast Box

Easily add or reduce ballast with this heavy-duty box.

Optional ballast box extension available for category 1 boxes.



Quik-Tatch Weights, 42 lb (19.1 kg) and 70 lb (32.7 kg)

Add some extra weight to the front of the machine easily and securely with Quik-Tatch weights.



Rear Wheel Weights

Weight for ballast to help keep all four wheels on the ground.



Telescoping Draft Links

Reduce the amount of effort to attach 3-point implements, making small adjustments without moving the tractor.

Not compatible with iMatch™ Quick Hitch.



Top And Tilt

Allows hydraulic positioning, left/right and forward/backward, from the operator's seat using the loader joystick. Ideal for use in box blade or rear blade applications.

3R Only.



Front Fenders and Rear Fender Extensions

Keep it clean by protecting the tractor and the implements from debris flying off the tractor tires.

Rear fender extensions shown.
3R Only.




Hood Guard

Protect your hood from limbs and brush. Because your hood stands between the harsh, off-road world and your engine.



Tire Chains

For better traction in snow, ice and tough conditions.



Drawbar

Attaches to the back of your 3 Series Tractor and makes hauling and towing a breeze.

HELP YOURSELF

The full list of our implements and attachments would rival the longest to-do list. Let TipsNotebook.com show you how to use them.

For the full list, visit JohnDeere.com, JohnDeere.ca or talk to your John Deere Dealer today.

Maintenance Parts



Filter Pak

The key to do-it-yourself maintenance when changing your tractor filters.



Plus-50™ II Oil

The only engine oil you really ever need on the farm, in the field, or on the highway.



Battery

John Deere StrongBox™ Batteries and high performance batteries are a versatile, reliable solution. Economy options available.

Cell Phone Mount Kit

Keep your hands free and your phone at hand.
3R Cab Only

Tablet Mount Kit

Keep your hands free and your tablet at hand.
3R Cab Only

Stereo

AM/FM, Weatherband, Satellite, tablet or smart phone-ready. Play it again, Sam.

3R Cab Only

Cruise Control Kit

For MY18 and newer Tractors. Allows you to easily set your ground speed.

3-Point Tractor Receiver Hitch

For height adjustability and towing without the drawbar.

7-Pin Trailer Connector

Turn signal and position indicator all connect through here.
3R Only

Air Seat Suspension Kit

Sit down and make yourself comfortable. Cab and Open Operator Station models available.

3R Only

Large Seat Cover

By protecting your seat, many comfortable years are sure to follow.

The Augusta Georgia Factory

All 3E and 3R Tractors are **designed, assembled, tested and distributed** out of Augusta Georgia using foreign and domestic parts. These tractors are built to last. Learn more about how we run at JohnDeere.com/3Series or JohnDeere.ca/3Series.



6-YEAR / 2,000 HOUR LIMITED POWERTRAIN WARRANTY

We're backing these tractors with a reliable 6-Year Powertrain Warranty.¹ It's standard, comes at no cost, and covers both residential AND commercial use. It's just one more reason why—Nothing Runs Like a Deere.[™]

¹ All Compact Utility Tractors purchased new from an authorized John Deere Dealer come standard with a 6 year/2000 hour (whichever comes first) Powertrain Warranty. See the Limited Warranty for New John Deere Turf & Utility Equipment at dealer for details.

POWERGARD[™] PROTECTION PLANS*

Protect your 1 Series Tractor with a PowerGard[™] Protection Plan. It provides parts and labor coverage up to five years beyond your manufacturer's warranty. And if you sell your machine before coverage term ends, the remaining coverage is fully transferable to the next owner—adding value to resale or trade-in.

RESIDENTIAL (U.S.)

Offers same coverage as factory warranty; \$0 deductible and no out of pocket costs on covered repairs; transportation for repairs covered by factory warranty or extended repair protection.

AGRICULTURE EQUIPMENT (CANADA)

Offers same bumper-to-bumper coverage as factory warranty (excludes some specific items); excludes high-wear/maintenance type of parts/components; subject to a low (or no) deductible.

| | 3025D | 3035D | 3043D | 3025E |
|---|--|--|--|--|
| ENGINE | | | | |
| Type | 3TNV88F-EPJPT Yanmar® Diesel Engine | 3TNV88F-EPJPT Yanmar® Diesel Engine | 3TNV88F-EPJPT Yanmar® Diesel Engine | 3TNV88F-EPJTI Yanmar® Diesel Engine |
| Horsepower | 24.72 (18.2 kW) ⁵ | 34.7 (25.5 kW) ⁵ | 42.2 (31 kW) ⁵ | 24.72 (18.2 kW) ⁵ |
| PTO HP Geared Transmission | 20.7 (15.4 kW) | 30.4 (22.7 kW) | 46.3 (27.1 kW) | — |
| PTO HP Geared Transmission | — | — | — | 19.4 (14.4 kW) |
| Rated Speed, rpm | 2400 | 2800 | 2800 | 2400 |
| Engine Displacement | 100.2 cu. in. (1.64 L) | 100.2 cu. in. (1.64 L) | 95.8 cu. in. (1.57 L) | 100.2 cu. in. (1.64 L) |
| Battery Power | 12V, 600 CCA | 12V, 600 CCA | 12V, 600 CCA | 12V, 500 CCA |
| Alternator | 55 A | 55 A | 55 A | 55 A |
| HYDRAULICS | | | | |
| Steering | 3.8 gpm (14.4 L/min) | 4.4 gpm (16.8 L/min) | 4.4 gpm (16.8 L/min) | 4 gpm (15 L/min) |
| Implement | 5.1 gpm (19.2 L/min) | 5.9 gpm (22.4 L/min) | 5.9 gpm (22.4 L/min) | 5.3 gpm (20.2 L/min) |
| Total Capacity | 8.9 gpm (33.6 L/min) | 10.3 gpm (39.2 L/min) | 10.3 gpm (39.2 L/min) | 9.3 gpm (35.2 L/min) |
| Lift capacity (24 in. Behind Center Link) | 1670 lb (757.4 kg) | 1670 lb (757.4 kg) | 1670 lb (757.4 kg) | 1356 lb (615 kg) |
| TRANSMISSION | | | | |
| Standard | Gear Transmission (8F-8R) | Gear Transmission (8F-8R) | Gear Transmission (8F-8R) | Hydrostatic-2 Range |
| Optional | NA | NA | NA | NA |
| Final Drive | Spur Gear | Spur Gear | Spur Gear | Spur Gear |
| Brakes | Wet Disc | Wet Disc | Wet Disc | Wet Disc |
| Steering | Power | Power | Power | Power |
| POWER TAKE-OFF (PTO) | | | | |
| PTO Type | Transmission Driven With Overrunning Clutch | Transmission Driven With Overrunning Clutch | Transmission Driven With Overrunning Clutch | Independent |
| PTO | Rear 540 | Rear 540 | Rear 540 | Rear 540 |
| PTO Options | — | — | — | — |
| REAR HITCH | | | | |
| Type | Category 1 | Category 1 | Category 1 | Category 1 |
| Control Type | Position | Position | Position | Position |
| WEIGHT | | | | |
| Open Station 4WD/MFWD | 2778 lb (1260 kg) | 2800 lb (1271 kg) | 2800 lb (1271 kg) | 2222 lb (1008 kg) |
| Cab MFWD | — | — | — | — |
| LOADER | | | | |
| Max Height Lift Capacity at Pivot | 1186 lb ⁵ (539 kg) ⁶ | 1186 lb ⁵ (539 kg) ⁶ | 1186 lb ⁵ (539 kg) ⁶ | 1186 lb (539 kg) ⁶ |

⁵The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information.
⁶Rated engine horsepower (ISO) per SAE J1995. ⁵Lift values based on 320R loader. For a complete list of loader specifications see your dealer. ⁶Certain limitations and exclusions may apply. For complete terms and conditions, please refer to www.johndeere.com/pppr or www.johndeere.ca/pppr



JOHN DEERE FINANCING

In the world of loader work, digging trenches, clearing ground, leveling driveways, putting in fences, sweeping sidewalks and caring for livestock and crops, you can count on John Deere Financial. Just like John Deere Tractors, our roots run deep in some of the healthiest, high producing fields and farms in the world and we're proud of the long-standing relationships we have with small farmers and large farming operations alike.

The lay of the land of commercial landscapers, sports turf complexes, golf courses, municipalities and federal governments are no strangers to us either. Let's dig in. Put the strength and flexibility of John Deere Financing behind your purchase. We know the landscape you work in and we're committed to helping you get what you need. You can bank on it.

| | 3032E | 3038E | 3033R | 3039R | 3046R |
|--|--------------------------------------|--------------------------------------|----------------------------------|--------------------------------------|---------------------------------------|
| ENGINE | | | | | |
| Type | 3TNV88C-NJT Yanmar® Diesel Engine | 3TNV86T-NJT Yanmar® Diesel Engine | 3TNV88C Yanmar® Diesel Engine | 3TNV86CT CR Yanmar® Diesel Engine | 3TNV86CHT CR Yanmar® Diesel Engine |
| Horsepower | 31.1 (22.9 kW) ⁵ | 37.2 (27.4 kW) ⁵ | 32.2 (23.7 kW) ⁵ | 38.7 (28.5 kW) ⁵ | 45.3 (33.3 kW) ⁵ |
| PTO HP Geared Transmission | 25.0 (18.6 kW) | 30.0 (22.4 kW) | 24.3 (18.1 kW) | 31.1 (23.2 kW) | 36.6 (27.3 kW) |
| Rated Speed, rpm | 2500 | 2500 | 2600 | 2600 | 2600 |
| Engine Displacement | 100.2 cu. in. (1.64 L) | 95.7 cu. in. (1.57 L) | 100.2 cu. in. (1.64 L) | 95.7 cu. in. (1.57 L) | 95.7 cu. in. (1.57 L) |
| Battery Power | 12V, 500 CCA | 12V, 500 CCA | 12V, 500 CCA | 12V, 500 CCA | 12V, 500 CCA |
| Alternator | 55 A | 55 A | 75 A | 75 A | 75 A |
| HYDRAULICS | | | | | |
| Steering | 4 gpm (15 L/min) | 4 gpm (15 L/min) | 6.2 gpm (23.5 L/min) | 6.2 gpm (23.5 L/min) | 6.2 gpm (23.5 L/min) |
| Implement | 5.3 gpm (20.2 L/min) | 5.3 gpm (20.2 L/min) | 9.1 gpm (34.3 L/min) | 9.1 gpm (34.3 L/min) | 9.1 gpm (34.3 L/min) |
| Total Capacity | 9.3 gpm (35.2 L/min) | 9.3 gpm (35.2 L/min) | 15.3 gpm (57.6 L/min) | 15.3 gpm (57.6 L/min) | 15.3 gpm (57.6 L/min) |
| Lift capacity (24 in. Behind Center Link) | 1356 lb (615 kg) | 1356 lb (615 kg) | 2200 lb (998 kg) | 2200 lb (998 kg) | 2200 lb (998 kg) |
| TRANSMISSION | | | | | |
| Standard | Hydrostatic-2 Range | Hydrostatic-2 Range | PowrReverser 12F/12R | PowrReverser 12F/12R | eHydro |
| Optional | NA | NA | Hydrostatic-3 Range | Hydrostatic-3 Range | NA |
| Final Drive | Spur Gear | Spur Gear | Helical Gear | Helical Gear | Helical Gear |
| Brakes | Wet Disc | Wet Disc | Wet Disc | Wet Disc | Wet Disc |
| Steering | Power | Power | Power | Power | Power |
| POWER TAKE-OFF (PTO) | | | | | |
| PTO Type | Independent | Independent | Independent | Independent | Independent |
| PTO | Rear 540 | Rear 540 | Rear 540 | Rear 540 | Rear 540 |
| PTO Options | — | — | Mid | Mid | Mid |
| REAR HITCH | | | | | |
| Type | Category 1 | Category 1 | Category 1 | Category 1 | Category 1 |
| Control Type | Position | Position | Position | Position | Position |
| WEIGHT | | | | | |
| Open Station 4WD/MFWD | 2222 lb (1008 kg) | 2222 lb (1008 kg) | 2900 lb (1316 kg) | 2900 lb (1316 kg) | 2900 lb (1316 kg) |
| Cab MFWD | — | — | 3570 lb (1619 kg) | 3570 lb (1619 kg) | 3570 lb (1619 kg) |
| LOADER | | | | | |
| Max Height Lift Capacity at Pivot | 1186 lb (539 kg) ⁶ | 1186 lb (539 kg) ⁶ | 1598 lb (725 kg) ⁶ | 1598 lb (725 kg) ⁶ | 1598 lb (725 kg) ⁶ |

A John Deere 3039R tractor with a yellow snow blower attachment is parked in a snowy field. The tractor is green with yellow accents, including the seat and wheels. The background features snow-covered mountains and a clear blue sky. A horse is visible in the distance behind a fence.

JohnDeere.com/3Series

JohnDeere.ca/3Series

John Deere, the leaping deer symbol and John Deere's green and yellow trade dress are the trademarks of Deere & Company.

2022451 (22-02)